DIALOG(R) File 351: Derwent WPI (c) 2005 Thomson Derwent. All rts. reserv.

007161896

WPI Acc No: 1987-158905/198723

XRAM Acc No: C87-066337

PVC compsn. contains organo-polysiloxane block or statistical polymer - having omega-hydroxy-alkyl-siloxy gps. added as defoamer or lubricant

Patent Assignee: RHONE POULENC SPECIALITES CHIM (RHON )

Inventor: CARETTE L; GAY M

Number of Countries: 014 Number of Patents: 004

Patent Family:

Patent No Date Applicat No Kind Kind Date Week EP 225261 A 19870610 EP 86420262 A 19861023 198723 B 19870507 FR 8516334 FR 2589476 Α Α 19851030 198724 JP 62106943 Α 19870518 JP 86253897 Α 19861027 198725 JP 88043423 В 19880830 198838

Priority Applications (No Type Date): FR 8516334 A 19851030

Cited Patents: EP 43965; JP 58180555; US 4231909

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

EP 225261 A F 13

Designated States (Regional): AT BE CH DE ES FR GB GR IT LI LU NL SE

Abstract (Basic): EP 225261 A

The compsns. contain, per 100pts. PVC, 0.001-2, partic. 0.005-1 pt. at least one polyorganosiloxane (I) block or statistical polymer of average formula (I) R = Me or Ph, at least 60 mol % being Me; R1 = linear or branched 1-18C alkylene hydrocarbon gp.; p = 1-30; q = 1-100. (I) has no. average mol. wt. 600-10,000. R1 = trimethylene or 2-methyltrimethylene, R = Me, p = 2-20 and q = 2-30. Compsn. is PVC plastisol or rigidor plasticised PVC.

USE/ADVANTAGE - (I) as defoaming agent and/or lubricatant for PVC plastisols or rigid or plasticised PVC (claimed). (I) does not exude and is not readily deposited in moulding machine, avoiding need for cleaning to prevent thermal decomposition of deposits; weldability of compsn. is unaffected.

0/0

Title Terms: PVC; COMPOSITION; CONTAIN; ORGANO; POLYSILOXANE; BLOCK; STATISTICAL; POLYMER; OMEGA; HYDROXY; ALKYL; SILOXY; GROUP; ADD; DEFOAM; LUBRICATE

Derwent Class: A14; A26; E11

International Patent Class (Additional): C08G-077/16; C08J-003/00;

C08K-005/54; C08L-027/06; C08L-083/06

File Segment: CPI